AcrEase Finish & Rough Cut Mower Specifications 2008				
Model	E60B	H60B	H60H	
Class Mower	Homeowner (Finish)	Homeowner (Finish)	Homeowner (Finish)	
Engine Make	Briggs & Stratton	Briggs& Stratton OHV	Honda	
Engine Model	Intek	Intek AVS	GXV390	
Engine HP	13.0	17.5	13.0	
Lubrication Method	Splash	Splash	Splash	
Engine Rated Hours	600	1000	1600	
Sustained Angle Cut	25 Degree	25 Degree	20 Degree	
Electric Start	No	Yes	No	
Number Blades	3 - 20"	3 - 20"	3 – 20"	
Blade Tip Speed	17,500 rpm	17,500 rpm	17,500 rpm	
Cutting Width	58"	58"	58"	
Cutting Height	1.0"-4.0"	1.0" - 4.0"	1.0" - 4.0"	
Hitch Offset	38"-60"	38" - 60"	38" - 60"	
Blade Clutch	Manual	Centrifugal	Centrifugal	
Clutch Engagement	Manual	1850 rpm	1850 rpm	
Drive Method	1 B V Belt	1 B V Belt	1 B V Belt	
Deck Thickness	11 GA	11 GA	11 GA	
Deck Top Plate	11 GA	11 GA	11 GA	
Weight	335 lbs Crated (390 lbs)	325 lbs Crated (396 lbs)	325 lbs Crated (396lbs)	
Pneumatic Rear	Yes	Yes	Yes	
Tires	(13/500 x 6, 2 ply turf)	(13/500 x 6, 2 ply turf)	(13/500 x 6, 2 ply turf)	
Pneumatic Front	Yes	Yes	Yes	
Tires	9/350 x 4, 4 ply slick	9/350 x 4, 4 ply slick	9/350 x 4, 4 ply slick	
Number Anti-Scalp Wheels Under Deck	6 ^(4 front, 2 rear)	6 ^(4 front, 2 rear)	6 ^(4 front, 2 rear)	
Hour Meter/Tach	No	No	No	
Oil Pressure Shut Off	No	No	No	
Fuel Tank Size	1.0 Gal.	3-3/4 Gal.	3-3/4 Gal.	
Replaceable Spindle Bearings	Yes	Yes	Yes	
Spindle Shaft Size	25mm	25mm	25mm	
Warranty All AcrEase Mowers have a two year engine warranty, and a one year mower warranty				

Price	\$1,995	\$2,295	\$2,695
ATV Hitch	\$ 100.00	\$ 100.00	\$ 100.00
Lawn & Garden Hitch	\$ 130.00	\$ 130.00	\$ 130.00
Optional Floatation Kit	•		
Front and Rear	\$ 200.00	\$ 200.00	\$ 200.00
D! .4!l41	1 N	Danta Carra 204 C Main C4 I	

Distributed by: NeedLawnMowerParts.Com 304 S Main St. Lynchburg, OH 45142 Tel: 866-660-7278 Fax: 937-364-9804 Email customerservice@needlawnmowerparts.com Price List Effective May 1, 2008

AcrEase Finish & Rough Cut Mower Specifications 2008				
Model	H60T	C60K	Pro-60K	
Class Mower	Homeowner (Finish)	Commercial (Finish)	Pro Commercial (Finish)	
Engine Make	Tecumseh OHV	Kohler	Kohler	
Engine Model	Enduro	Command CV 493	Command CV 493	
Engine HP	13.5	18.0	18.0	
Lubrication Method	Pressure/Filter	Pressure/Filter	Pressure/Filter	
Engine Rated Hours	600	1600	1600	
Sustained Angle Cut	25 Degree	45 Degree	45 Degree	
Electric Start	Yes	Yes	Yes	
Number Blades	3 - 20"	3 – 20"	3 - 20"	
Blade Tip Speed	17,500 rpm	17,500 rpm	17,500 rpm	
Cutting Width	58"	58"	58"	
Cutting Height	1.0"-4.0"	1.0"-4.0"	1.5 - 5.0" Insta-Crank	
Hitch Offset	38"-60"	38"-60"	38" - 60"	
Blade Clutch	Centrifugal	Centrifugal	Electric	
Clutch Engagement	1850 rpm	1850	Switched	
Drive Method	1 B V Belt	1 B V Belt	1 B V Belt	
Deck Thickness	11 GA	10 GA (1/4") + Top Plate	10 GA	
Deck Top Plate	11 GA	7 GA	7 GA	
Weight	325 lbs Crated (396 lbs)	380 lbs Crated (468 lbs)	545 lbs Crated (615 lbs)	
Pneumatic Rear	Yes	Yes	Yes	
Tires	(13/500 x 6, 2 ply turf)	(13/500 x 6, 2 ply turf)	(15/600 x 6, 4 ply turf)	
Pneumatic Front	Yes	Yes	Yes	
Tires	9/350 x 4, 4 ply slick	9/350 x 4, 4 ply slick	13/500 x 6, slick	
Number Anti-Scalp Wheels Under Deck	6 ^(4 front, 2 rear)	6 ^(4 front, 2 rear)	6 ^(4 front, 2 rear)	
Hour Meter/Tach	No	Yes	Yes	
Oil Pressure Shut Off	No	Yes	Yes	
Fuel Tank Size	3-3/4 Gal.	3-3/4 Gal.	3-3/4 Gal.	
Replaceable Spindle Bearings	Yes	Yes	Sealed	
Spindle Shaft Size	25mm	25mm	25mm	
Warranty All AcrEase M	owers have a two year e	ngine warranty, and a one	year mower warranty	

Price	\$2,295	\$3,195	\$3,695
ATV Hitch	\$ 100.00	\$ 100.00	\$ 100.00
Lawn & Garden Hitch	\$ 130.00	\$ 130.00	\$ 161.00
Optional Floatation Kit	•		
Front and Rear	\$200.00	\$200.00	\$ 240.00
		D . C	11 OTT 151 10

Distributed by: NeedLawnMowerParts.Com 304 S Main St. Lynchburg, OH 45142 Tel: 866-660-7278 Fax: 937-364-9804 Email customerservice@needlawnmowerparts.com
Price List Effective May 1, 2008

AcrEase Finish & Rough Cut Mower Specifications 2008			
Model	C60H	MR44B	
Class Mower	Commercial (Finish)	Rough Cut (Rear Discharge)	
Engine Make	Honda	Briggs & Stratton	
Engine Model	GXV390	Intek OHV	
Engine HP	13.0	17.5	
Lubrication Method	Splash	Splash	
Engine Rated Hours	1600	1000	
Sustained Angle Cut	20 Degree	25 Degree	
Electric Start	Yes	Yes	
Number Blades	3 - 20"	2 – 23"	
Blade Tip Speed	17,500 rpm	19,000 rpm	
Cutting Width	58"	44"	
Cutting Height	1".0 - 4.0"	2.0" – 8.0"	
Hitch Offset	38" - 60"	0" – 44"	
Blade Clutch	Centrifugal	Manual	
Clutch Engagement	1850 RPM	Manual	
Drive Method	1 B V Belt	1 B V Belt	
Deck Thickness	11 GA	10 GA (1/4") + Top Plate	
Deck Top Plate	11 GA	1/4"	
Weight	380 lbs Crated (468 lbs)	520 lbs Crated (600 lbs)	
Pneumatic Rear	Yes	Yes	
Tires	15/600 x 6, 2 ply turf	15/600 x 6, 2 ply turf	
Pneumatic Front	Yes	Yes	
Tires	9/350 x 4, 4 ply slick	5.30/4.50 x 6	
Number Anti-Scalp Wheels Under Deck	N/A	N/A	
Hour Meter	No	No	
Oil Pressure Shutoff	No	No	
Fuel Tank Size	3-3/4 Gal.	3-3/4 Gal.	
Replaceable Spindle Bearings	Yes	Yes	
Spindle Shaft Size	30mm	30mm	
Warranty All AcrEase Mo	wers have a two year engine warranty, and a	one year mower warranty	

Price	\$3,195		\$2,595
ATV Hitch	\$ 100.00		Included
Lawn& Garden Hitch	\$ 130.00	Wetlands Kit	\$ 335.00
Floatation Kit	\$ 200.00	Floatation Kit	\$ 375.00
		Electric Lift Kit	\$ 530.00

Distributed by: NeedLawnMowerParts.Com 304 S Main St. Lynchburg, OH 45142 Tel: 866-660-7278 Fax: 937-364-9804 Email customerservice@needlawnmowerparts.com

Price List Effective May 1, 2008

Specification and Price Sheet Part Number AE200814

AcrEase Rough Cut Mower Specifications 2008				
Model	MR44K	MR55B-17	MR55B-22	
Class Mower	Rough Cut (Rear Discharge)	Rough Cut (Rear Discharge)	Rough Cut (Rear Discharge)	
Engine Make	Kohler	Briggs & Stratton	Briggs & Stratton	
Engine Model	Command OHV	Intek OHV	Intek OHV	
Engine HP	18.0	17.5	22.0	
Lubrication Method	Pressure/Filter	Pressure/Filter	Pressure/Filter	
Engine Rated Hours	1600	1000	1000	
Sustained Angle Cut	45 Degree	25 Degree	25 Degree	
Electric Start	Yes	Yes	Yes	
Number Blades	2-23"	2-30"	2-30"	
Blade Tip Speed	19,000 rpm	19,000 rpm	19,000 rpm	
Cutting Width	44"	57"	57"	
Cutting Height	2.0" - 8.0"	2.0" – 8.0"	2.0"-8.0"	
Hitch Offset	0"-44"	0" – 57"	0" – 57"	
Blade Clutch	Manual	Manual	Manual	
Clutch Engagement	Manual	Manual	Manual	
Drive Method	1 B V Belt	1 B V Belt	1 B V Belt	
Deck Thickness	10 GA (1/4") + Top Plate	10 GA (1/4") + Top Plate	10GA (1/4") + Top Plate	
Deck Top Plate	1/4"	1/4 "	1/4"	
Weight	520 lbs Crated (600 lbs)	500 lb = 0 == 4 = 1 (070 lb =)		
**************************************	520 lbs Crated (600 lbs)	580 lbs Crated (673 lbs)	580 lbs Crated (673 lbs)	
Pneumatic Rear	Yes	Yes	Yes	
Pneumatic Rear Tires	Yes 15/600 x 6, 2 ply turf	Yes 15/600 x 6, 2 ply	Yes 15/600 x 6, 2ply	
Pneumatic Rear Tires Pneumatic Front	Yes 15/600 x 6, 2 ply turf Yes	Yes 15/600 x 6, 2 ply Yes	Yes 15/600 x 6, 2ply Yes	
Pneumatic Rear Tires Pneumatic Front Tires	Yes 15/600 x 6, 2 ply turf Yes 5.30/4.50 x 6	Yes 15/600 x 6, 2 ply Yes 5.30/4.50 x 6	Yes 15/600 x 6, 2ply Yes 5.30/4.50 x 6	
Pneumatic Rear Tires Pneumatic Front	Yes 15/600 x 6, 2 ply turf Yes	Yes 15/600 x 6, 2 ply Yes	Yes 15/600 x 6, 2ply Yes	
Pneumatic Rear Tires Pneumatic Front Tires Number Anti-Scalp	Yes 15/600 x 6, 2 ply turf Yes 5.30/4.50 x 6	Yes 15/600 x 6, 2 ply Yes 5.30/4.50 x 6	Yes 15/600 x 6, 2ply Yes 5.30/4.50 x 6	
Pneumatic Rear Tires Pneumatic Front Tires Number Anti-Scalp Wheels Under Deck	Yes 15/600 x 6, 2 ply turf Yes 5.30/4.50 x 6 N/A	Yes 15/600 x 6, 2 ply Yes 5.30/4.50 x 6 N/A	Yes 15/600 x 6, 2ply Yes 5.30/4.50 x 6 N/A	
Pneumatic Rear Tires Pneumatic Front Tires Number Anti-Scalp Wheels Under Deck Hour Meter Oil Pressure Shutoff Fuel Tank Size	Yes 15/600 x 6, 2 ply turf Yes 5.30/4.50 x 6 N/A	Yes 15/600 x 6, 2 ply Yes 5.30/4.50 x 6 N/A	Yes 15/600 x 6, 2ply Yes 5.30/4.50 x 6 N/A	
Pneumatic Rear Tires Pneumatic Front Tires Number Anti-Scalp Wheels Under Deck Hour Meter Oil Pressure Shutoff Fuel Tank Size Replaceable Spindle	Yes 15/600 x 6, 2 ply turf Yes 5.30/4.50 x 6 N/A Yes Yes	Yes 15/600 x 6, 2 ply Yes 5.30/4.50 x 6 N/A No	Yes 15/600 x 6, 2ply Yes 5.30/4.50 x 6 N/A No	
Pneumatic Rear Tires Pneumatic Front Tires Number Anti-Scalp Wheels Under Deck Hour Meter Oil Pressure Shutoff Fuel Tank Size	Yes 15/600 x 6, 2 ply turf Yes 5.30/4.50 x 6 N/A Yes Yes 3-3/4 Gal.	Yes 15/600 x 6, 2 ply Yes 5.30/4.50 x 6 N/A No No No 3-3/4 Gal.	Yes 15/600 x 6, 2ply Yes 5.30/4.50 x 6 N/A No No No 3-3/4 Gal.	

Price	\$3,295	\$3,195	\$3,395
ATV Hitch	Included	Included	Included
Wetlands Kit	\$ 350.00	\$ 350.00	\$ 350.00
Floatation Kit	\$ 375.00	\$ 375.00	\$ 375.00
Electric Lift Kit	\$ 690.00	\$ 690.00	\$ 690.00

Distributed by: NeedLawnMowerParts.Com 304 S Main St. Lynchburg, OH 45142 Tel: 866-660-7278 Fax: 937-364-9804 Email customerservice@needlawnmowerparts.com Price List Effective May 1, 2008

AcrEase Rough Cut Mower Specifications 2008				
Model	MR55K	MR55H	MR55KE	
Class Mower	Rough Cut (Rear Discharge)	Rough Cut (Rear Discharge)	Rough Cut (Rear Discharge)	
Engine Make	Kohler	Honda	Kohler	
Engine Model	Command OHV	GXV 610 OHV	Command OHV	
Engine HP	20.0	18.0	20.0	
Lubrication Method	Pressure/Filter	Pressure/Filter	Pressure/Filter	
Engine Rated Hours	1600	1600	1600	
Sustained Angle Cut	45 Degree	20 Degree	45 Degree	
Electric Start	Yes	Yes	Yes	
Number Blades	2-30"	2-30"	2-30"	
Blade Tip Speed	19,000 rpm	19,000 rpm	19,000 rpm	
Cutting Width	57"	57"	57"	
Cutting Height	2.0" - 8.0"	2.0" – 8.0"	2.0"-8.0"	
Hitch Offset	0"-57"	0" – 57"	0" – 57"	
Blade Clutch	Manual	Manual	Electric	
Clutch Engagement	Manual	Manual	Electric 200 ft/lbs	
Drive Method	1 B V Belt	1 B V Belt	1 B V Belt	
Deck Thickness	10 GA (1/4") + Top Plate	10 GA (1/4") + Top Plate	10GA (1/4") + Top Plate	
Deck Top Plate	1/4"	1/4 "	1/4"	
Weight	580 lbs Crated (715 lbs)	580 lbs Crated (715 lbs)	580 lbs Crated (715 lbs)	
Pneumatic Rear Tires	Yes 15/600 x 6, 2 ply turf	Yes 15/600 x 6, 2 ply	Yes 15/600 x 6, 2ply	
Pneumatic Front Tire		Yes	Yes	
w/ sealed bearings	5.30/4.50 x 6	5.30/4.50 x 6	5.30/4.50 x 6	
Number Anti-Scalp Wheels Under Deck	N/A	N/A	N/A	
Hour Meter	Yes	No	No	
Oil Pressure Shutoff	No	No	No	
Fuel Tank Size	3-3/4 Gal.	3-3/4 Gal.	3-3/4 Gal.	
Greasable Spindles	Yes	Yes	Yes	
Spindle Shaft Size	30mm	30mm	30mm	
Warranty All AcrEase	Mowers have a two year e	ngine warranty, and a on	e year mower warranty	

Price	\$4,295	\$4,395	\$4,495
Tow Hitch	Included	Included	Included
	Wetlands Kit	Wetlands Kit	Wetlands Kit
	\$335.00	\$335.00	\$335.00

Distributed by: NeedLawnMowerParts.Com 304 S Main St. Lynchburg, OH 45142 Tel: 866-660-7278 Fax: 937-364-9804 Email customerservice@needlawnmowerparts.com Price List Effective May 1, 2008

Specification and Price Sheet Part Number AE200814

Till-Ease Specifications 2008			
Model	543		2148
Tool Type	Chisel Plow/Cultivator		Cultipacker
Electric Lift with			
Operator Controls	Yes	Lift Method	Flip Over
Number of			Cast Iron with
Cutting Coulters	5	Packer Wheels	Crusher Knobs
Cutting Coulter		Number of Cast	
Size (Ag Quality	13.5"	Iron Packer Wheels	21
Number of			
Shanks (Adjustable)	5	Packer Wheel Size	9.5"
Shank Type		Packer Wheel Shaft	
Rigid	1 3/8" Square Solid	Bearings	1 3/4" Greasable
Adjustable Quck			
Remove Shanks	Yes		
Maximum Depth	6"		
Cultivator Sweep			
Size (Ag Quality)	9" wide		
Reversable Chisel			
Point Sweep Size	1 ¾" Hitch Offset		
Cutting Width	43"	Width	48"
Tongue Adjustment			
Method	"Stay Level" Top Link		
Tongue Hitch		Tongue Hitch	
Method	Quick Remove Pin	Method	Quick Remove Pin
Pneumatic	Yes	Pneumatic	Yes
Tires	(15/600x6, 4 ply turf)	Tires	(13/500 x 6, 2 ply turf
Attachment			· ·
Receivers	Yes		
Weight Racks	Yes		Yes
Weight	330# Weight Racks		272# Weight Racks
l •	Empty		Empty
Warranty	One Year (Non-Commercial)	Warranty	One Year (Non-Commercial)

Price	\$2	2,195	\$	845
Optional Drag				
Harrow	\$	295.00		
Optional Turning				
Shovel Kit (5)	\$	55.00		
Distribute	ed by:	NeedLawnMowerParts.Com	304 S Main St. Lynchburg, OF	I 45142

Tel: 866-660-7278 Fax: 937-364-9804 Email customerservice@needlawnmowerparts.com Price List Effective May 1, 2008
Specification and Price Sheet Part Number AE200814